

Product Styles and Sizes					Frame Styles				Frame Colors		Test Methods and Certifications					
Product Style	Configuration	Nominal Frame Depth	Minimum Size (actual DLO frame size)	Maximum Size (actual DLO frame size)	5/8" Flange	Integral Nail Fin	J-Channel	Equal Leg	White, Beige, Bronze, Black	Custom Colors	AAMA A440 & ASTM E1886/1996		TAS 201 / 202 / 203		Florida Product Approval	ENERGY STAR®
											Design Pressure	Keystone Certification	Design Pressure	Miami-Dade NOA		
Single Hung (SH5500)	O/X Equal	3-1/2"	16-1/4" x 23-1/2"	52-1/8" x 84"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
	O/X Proview	3-1/2"	16-1/4" x 28"	52-1/8" x 84"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
	O/X Custom Sash	3-1/2"	16-1/4" x 28"	52-1/8" x 91-13/16"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
Double Hung (DH5560)	X/X Equal	3-1/2"	16-1/4" x 26-1/2" or 17-1/2" x 23-1/2"	52-1/8" x 84"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
	X/X Proview	3-1/2"	16-1/4" x 31" or 17-1/2" x 28"	52-1/8" x 75"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
	X/X Custom Sash	3-1/2"	16-1/4" x 32"	52-1/8" x 86-3/8"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
Horizontal Roller (HR5510)	XO / OX Equal	3-1/2"	25-1/2" x 20-1/4" or 33-3/4" x 16-1/4"	75" x 72"	■	■	■	■	■	■	+65/-70	■	+65/-80 +65/-110*	■	■	■
	XOX 1/4-1/2-1/4	3-1/2"	45-1/8" x 17" or 47-3/4" x 16-1/4"	120" x 63"	■	■	■	■	■	■	+65/-70	■	+65/-110	■	■	■
	XOX 1/3-1/3-1/3	3-1/2"	35-1/4" x 17-1/4" or 38" x 16-1/4"	92" x 63"	■	■	■	■	■	■	+65/-70	■	+65/-110	■	■	■
	XOX Custom Sash	3-1/2"	35-1/4" x 17-1/4" or 38" x 16-1/4"	140" x 63"	■	■	■	■	■	■			+65/-110	■	■	■
Casement (CA5540)	X Standard Hinge	3-1/2"	17" x 20"	36" x 71-9/16" or 34-5/16" x 75"	■	■	■	■	■	■	+50/-50	■	+65/-66.5 +65/-70*	■	■	■
	X TrueHold Hinge	3-1/2"	17" x 20"	36" x 84"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
Awning (AW5540)	X	3-1/2"	21-1/4" x 16"	60" x 42"	■	■	■	■	■	■	+65/-70	■	+70/-110	■	■	■
				36" x 84"											+70/-110	■

* Maximum design pressure using comparative analysis on smaller sizes.

Product Styles and Sizes					Frame Styles				Frame Colors		Test Methods and Certifications						
Product Style	Configuration	Nominal Frame Depth	Minimum Size (actual DLO frame size)	Maximum Size (actual DLO frame size)	5/8" Flange	Integral Nail Fin	J-Channel	Equal Leg	White, Beige, Bronze, Black	Custom Colors	AAMA A440 & ASTM E1886/1996		TAS 201 / 202 / 203		Florida Product Approval	ENERGY STAR®	
											Design Pressure	Keystone Certification	Design Pressure	Miami-Dade NOA			
Picture Window / Architectural +	O	3-1/2"	10" x 16"	96" x 63" or 84" x 72"	■	■	■	■	■	■	+70/-70	■			■	■	
				Up to 42 sq. ft.										+70/-70 (Fin) +80/-110	■		
	O	3-1/2"	12-1/2" x 18"	96" x 63" or 84" x 72"	■	■	■	■	■	■	+70/-70	■			■	■	
				Up to 42 sq. ft.										+70/-70 (Fin) +80/-110	■		
Sliding Glass Door	(SGD5570)	By-Pass or Pocket and 90° or 135° Corners	2-track 5-7/8" 3-track 8-1/4" 4-track 10-5/8"	22-15/16" x 30" panel	5'0" x 10'0" panel				■	■	■	+100/-100	■	+100/-100	■	■	
Sliding Glass Door	(SGD5570NS)	By-Pass or Pocket and 90° Corners	2-track 5-7/8" 3-track 8-1/4" 4-track 10-5/8"	21-3/8" x 30" panel	5'0" x 10'0" panel					■	■	■	+60/-70	+60/-70*	■	■	
French Door	(FD555E)	X	4-9/16"	20" x 74"	38-3/4" x 96"					■**	■	+70/-70	■	+70/-70	■	■	
		XX	4-9/16"	36" x 74"	76" x 96"					■	■**	■	+70/-70	■	+70/-70	■	■
		O	4-9/16"	12" x 20" or 20" x 12"	40" x 111" or 111" x 40"					■	■**	■	+70/-70	■	+70/-70	■	■

+ Minimum/Maximum sizes may vary by shape. Refer to ClearQuote for specific shape sizes.

* Maximum design pressure using comparative analysis on smaller sizes.

** Black is only available on the exterior.